

DECLARATION OF PERFORMANCES Nº: 105291-162


- 1. Product:**
PEGOLAND DOS PORCELANICO GRIS
- 2. Manufacturer:**
GRUPO PUMA ESPAÑA SL located in:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com
- 3. Intended use:**
Improved cementitious adhesive with reduced slip and extended open time, Pegoland Dos Porcelánico Gris (C2TE). For the installation of interior and exterior floors, interior coatings and skirting boards, pool coatings, and overlays on interior floors. It adheres to all types of ceramic pieces, porcelain tiles, marble, granite, and natural stone.
- 4. Evaluation system:**
3
- 5. Notified bodies:**
Tests were carried out under type numbers 3001508 in January 2010 at CEMOSA nº 1377 (Málaga), and nº 09/1106-3220, 09/1074-3124 in January 2010, and nº 11/2647-659 in May 2011 at APPLUS nº 0370 (Barcelona), obtaining the same results for the product from all factories.
- 6. Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	Type E	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength	$\geq 1\text{N/mm}^2$	
Durability: - Tensile adhesion after water immersion - Tensile adhesion after heat aging - Tensile adhesion after freeze/thaw cycles	$\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$	
Hazardous substances:	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 6.
This declaration of features is issued under the sole responsibility of manufacturer stated in point 2.
Signed by and on manufacturer behalf:
Place and date of issue: Málaga, 17/04/2023



Technical director: Jose A. Ferre Martínez

 0370, 1377	
GRUPO PUMA ESPAÑA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 10	
PEGOLAND DOS PORCELANICO GRIS Nº: 105291-162 EN-12004:2007+A1:2012 Improved cementitious adhesive with reduced slip and extended open time, for floors and walls, suitable for interior and exterior applications.	
Reaction to fire:	Type E
Adhesion:	
- Initial tensile adhesion strength:	≥ 1N/mm ²
Durability:	
- Tensile adhesion after water immersion:	≥ 1N/mm ²
- Tensile adhesion after heat aging:	≥ 1N/mm ²
- Tensile adhesion after freeze/thaw cycles:	≥ 1N/mm ²
Hazardous substances:	See safety datasheet