

DECLARATION OF PERFORMANCES

Nº: 105290-161

1. Product:

PEGOLAND DOS PORCELANICO BLANCO

2. Manufacturer:

GRUPO PUMA ESPAÑA SL located in:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com

3. Intended use:

Cementitious adhesive improved with reduced slip and extended open time, Pegoland Dos Porcelánico Blanco (C2TE). Designed for the installation of interior and exterior floors, interior coatings and skirting boards, pool coatings, and overlays on interior floors. It provides adhesion for all types of ceramic pieces, porcelain tiles, marble, granite, and natural stone.

4. Evaluation system:

3

5. Notified bodies:

Tests were conducted under type numbers 2822688, 2822921 in August 2008, 3001509 in January 2010, 3101523, 3101524 in January 2011, 0201/01/2012/004313, and 0/71201861/1/01 in April and May 2012 at CEMOSA nº 1377 (Málaga). Additionally, tests were carried out under numbers 08/1074-3968, 08/3231-3085, 08/3231-3086 in April, September, and December 2008, and 11/2654-662 in May 2011 at APPLUS nº 0370 (Barcelona). The results obtained were consistent for the product across all factories.

6. Declared performances:

| Essential characteristics | Performance | Harmonised technical specification |
|--|--|------------------------------------|
| Reaction to fire: | Type E | EN-12004:2007+A1:2012 |
| Adhesion: - Initial tensile adhesion strength | ≥ 1N/mm ² | |
| Durability: - Tensile adhesion after water immersion - Tensile adhesion after heat aging - Tensile adhesion after freeze/thaw cycles | ≥ 1N/mm ² ≥ 1N/mm ² ≥ 1N/mm ² | |
| Hazardous substances: | See safety datasheet | |

The performances of the product identified in point 1 comply with the performance declared in point 6.


This declaration of features is issued under the sole responsibility of manufacturer stated in point 2.

Signed by and on manufacturer behalf:

Place and date of issue: Málaga, 17/04/2023



Technical director: Jose A. Ferre Martínez

| | |
|--|----------------------|
|  0370, 1377 | |
| GRUPO PUMA ESPAÑA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 08 | |
| PEGOLAND DOS PORCELANICO BLANCO Nº: 105290-161 EN-12004:2007+A1:2012 Improved cementitious adhesive with reduced slip and extended open time, for floors and walls, suitable for interior and exterior applications. | |
| Reaction to fire: | Type E |
| Adhesion: | |
| - Initial tensile adhesion strength: | ≥ 1N/mm ² |
| Durability: | |
| - Tensile adhesion after water immersion: | ≥ 1N/mm ² |
| - Tensile adhesion after heat aging: | ≥ 1N/mm ² |
| - Tensile adhesion after freeze/thaw cycles: | ≥ 1N/mm ² |
| Hazardous substances: | See safety datasheet |